




COMMODORE SS

Power Pedestal Models CD50200 & CD100200

Marina Electrical Equipment strives to stay on the cutting-edge of product development. Modern marinas require more electrical capability than ever before, and our flagship power pedestal, the "Commodore SS" is designed to fit that need. With the ability to supply dual voltages/phases at up to 500A each, the Commodore SS enables the marina to accommodate the diverse power requirements of the larger super-yachts.



Commodore SS Single Feed Mounting Detail


STANDARD DIMENSIONS: 48"H 14"W 14"D

STANDARD FEATURES

- Intertek-ETL Listed, tested in accordance with Underwriters Laboratories-231 standards, CAN/CSA Standard C22.2 No.29 and NFPA 303.
- Rugged, long-lasting 16-gauge 316L stainless steel NEMA 3RX main housing.
- Heavy-duty .1875" thick injection-molded polycarbonate top assembly.
- Limited 1-Year Warranty.
- Extra wide back-lit receptacle faceplate for easier plug-in.
- Highest quality twist-lock receptacles & circuit breakers.
- Highest quality 100-amp pin and sleeve receptacles (when 100-amp receptacles are selected).
- Industry-trusted 200-amp pin and sleeve receptacles (when 200-amp receptacles are selected).
- Patented pivoting receptacle faceplate assembly, which simplifies field-maintenance tasks such as replacing circuit breakers, receptacles or meter current transformer coils.
- Two photocell-controlled LED light fixtures with fuse protection
- 250-Amp rated copper stud-lug single phase 125/250V terminal block.
- Newly designed, highly functional dual hose/cable brackets, capable of holding min. 50' of standard 5/8" ID garden hose or 50' of 50-ampere, 4-wire shore power (S.O.) cord.
- Clean-looking flush-mounted access panels.
- Lockable polycarbonate weatherproof doors which shield the receptacles and circuit breakers from the elements while in use (as required by NFPA 303 and NEC Article 555).

OPTIONAL FEATURES

- Receptacle Options:
 - 20A, 125V Duplex GFCI.
 - 20A, 125V L5-20R Twist-Lock Shorepower.
 - 30A, 125V L5-30R Twist-Lock Shorepower.
 - 50A, 125V SS-1 Twist-Lock Shorepower.
 - 50A, 125/250V SS-2 Twist-Lock Shorepower.
 - 100A, 125/250V Pin and Sleeve Shorepower.
 - 100A, 125/250Y Pin and Sleeve Shorepower.
 - 100A, 480V Pin and Sleeve Shorepower.
 - 200A, 480V Pin and Sleeve Shorepower.
- Hardwire Cam-Type Connectors.
- Interlocking circuit breakers, ground fault circuit breakers.
- Dual phase terminal blocks - available to 500-Amp ratings each.
- 250-Amp rated copper stud-lug three phase 125/250V terminal block(s).
- Solid-state electric monitoring for sub-metering kWh consumption.
- Wireless NUCORE™ remote meter reading.
- Ground Fault Monitoring at each slip (patented).
- 250-Amp rated copper stud-lug three phase 125/250V terminal block.
- 250-Amp rated split terminal block.
- 3/4" IPS ball valve hose bibs.
- Hose bib vacuum breakers.
- Water metering.
- Phone, Cable TV, and/or Data ports.
- Amber or Clear Polycarbonate Lens.



Commodore SS Dual Feed Mounting Detail



Easy-Access Terminal Block



Extra-Wide Back-Lit Receptacle Faceplate

